



---

# MT500

## Product Catalogue

Doc.No: 100352708  
Version from: 01.02.2026

---

---

## Device



### MT500 Three Phase Current/Voltage Source

Inclusive adjustment and factory calibration for one mains frequency.

Ord.No. **1016732xx**

Calibration	Ord.No.	Add.Price
Factory 50 Hz	xx --> 00	0,00 EUR
Factory 60 Hz	xx --> 01	0,00 EUR
DAkKS 50 Hz	xx --> 02	1.012,00 EUR
DAkKS 60 Hz	xx --> 03	1.012,00 EUR

MT500 is designed for generation of test voltage and test current for one test specimen.

#### Configuration:

- 3~ phase voltage generation up to 300 V (AC)
- 3~ phase current generation up to 12 A (AC)
- Light and compact design

## Power Cords



### Power cord with protective earth "stackable safety plug to IEC 60320 C13", 2,5 m

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x black, 1x blue, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067609**



### Power cord "Class I grounded plug type E/F to IEC 60320 C13", 2,5 m

For supply via power socket.

- 1x class I grounded plug type E/F (CEE 7/7), straight
- 1x socket IEC 60320 C13

Ord.No. **M00481006**



### Power cord "Plug type B to IEC 60320 C13", 2,5 m

For supply via power socket.

- 1x plug type B
- 1x socket IEC 60320 C13

Ord.No. **X00006459**



**Power cord “Plug type I to IEC 60320 C13“, 2.5 m**

For supply via power socket.

- 1x plug type I (AS/NZS 3112, 3-pin)
- 1x socket IEC 60320 C13

Ord.No.

**X00006460**

**Power cord “Plug type G (BS 1363) to IEC 60320 C13“, 2.5 m**

For supply via power socket.

- 1x Plug type G (BS 1363)
- 1x socket IEC 60320 C13

Ord.No.

**X00009832**

**Power cord “Plug type D (BS 546) to IEC 60320 C13“, 1.8 m**

For supply via power socket.

- 1x Plug type D (BS 546)
- 1x socket IEC 60320 C13

Ord.No.

**100929900**

**Power cord “Plug type H” to IEC 60320 C13“, 1.8 m**

For supply via power socket.

- 1x Plug type H
- 1x socket IEC 60320 C13

Ord.No.

**100929903**

**Quick Connection Cable (see also Special Accessories)**



**Quick connection cable “current/rigid sleeve” for source, MT series, sloped, 2.5 m, phase colours: red/yellow/blue**

To prevent connecting faults on the instrument’s side.

- Instrument’s side: 1x 6-pin connector with anti-twist safeguard, 30° sloped.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x red, 2x yellow, 2x blue.
- Cable cross-section: 2.5 qmm

Ord.No.

**100023452**




**Quick connection cable for “voltage/rigid sleeve” for MT series, 2.5 m, phase colours: red/yellow/blue/black**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x red, 1x yellow, 1x blue, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023454**



**Quick connection cable “voltage/rigid sleeve” for source-instrument, MT series, 2.5 m, phase colours: red/yellow/blue/black**

For the connection of source and reference standard if they are used as separate devices.

Cable length between the devices is 1.65 m.

- Reference standard's side :
  - 1x 4-pin connector with anti-twist safeguard.
  - 1x 4-pin connector (slim) without anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x red, 1x yellow, 1x blue, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023456**



**Quick connection cable “current/rigid sleeve” for source-instrument, MT series, 2.5 m, phase colours: red/yellow/blue**

For the connection of source and reference standard if they are used as separate devices.

Cable length between the devices is 1.65 m.

- Instrument's side:
  - 1x 6-pin connector with anti-twist safeguard.
  - 1x 6-pin connector, 30° sloped, with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x red, 2x yellow, 2x blue.
- Cable cross-section: 2.5 qmm

Ord.No. **100023455**

## Current and Voltage Cables (see also Special Accessories)



**Laboratory cable with stackable plug, red, 2.0 m**

Measurement category III (CAT III).

- 2x stackable 4 mm plugs with rigid insulating sleeve
- Lead cross section: 2.5 qmm

Ord.No. **X00007597**



**Laboratory cable with stackable plug, yellow, 2.0 m**  
 Measurement category III (CAT III).  
 • 2x stackable 4 mm plugs with rigid insulating sleeve  
 • Lead cross section: 2.5 qmm

Ord.No. **X00006907**



**Laboratory cable with stackable plug, blue, 2.0 m**  
 Measurement category III (CAT III).  
 • 2x stackable 4 mm plugs with rigid insulating sleeve  
 • Lead cross section: 2.5 qmm

Ord.No. **X00007598**



**Laboratory cable with stackable plug, black, 2.0 m**  
 Measurement category III (CAT III).  
 • 2x stackable 4 mm plugs with rigid insulating sleeve  
 • Lead cross section: 2.5 qmm

Ord.No. **X00006910**

**Software**




**Software SSM3000 / MTVis**

The software runs under Windows 7 or 10.  
 • SSM3000: For external control via PC.  
 • MTVis: To readout and display saved data.

Ord.No. **100090720**


The software can be downloaded at [www.zera.de](http://www.zera.de).



**Software option for harmonic measurement, MT400/MT500**

The harmonic measurement displays the value and angle of each single harmonic (voltage and current) up to the 40<sup>th</sup> in a chart or a diagram. Additionally the sum of all harmonics is displayed.

Ord.No. **100078830**



**Software option for curve display, MT400/MT500**

For simultaneous display of two curves (voltage and/or current measurement channels). Via the curve display you can see at a glance if the fundamental frequency differs from the sinus curve.

Ord.No. **100078831**

## Connectors (see also Special Accessories)



### Accessories bag with connection adapters

01	Accessories bag	100214400	Ord.No.	<b>100023727</b>
03	Spring clip	100606760		
04	4 mm plug adapter (banana plug)	X00004962		
10	Adapter for terminal blocks	101584400		
10	Connecting terminals for current	X00011923		
03	4 mm test clips (crocodile clips), slim	X00009329		
03	4 mm test clips (crocodile clips), wide	X00010059		
10	Fuse, 3.15 A, 5 mm x 20 mm, time-lag	M00460252		

## Transport (see also Special Accessories)



### Transport Case for MT400 / MT500, with cable case

Aluminum case with inlet from rigid foam, designed for

- 1 Instrument
- Accessories

Overall dimensions:

44 cm x 47 cm x 25 cm (H x W x D)

*Please clarify whether the case size is suitable for the ordered accessories.*

Ord.No. **100023960**



### Transport Bag for MT400 / MT500

Nylon bag which is special designed for the instrument.

The bag protects against dust and scratches.

The bag is designed for 1 Instrument

Overall dimensions:

34 cm x 29 cm x 23,5 cm (H x W x D)

Ord.No. **100062802**

## Standard Accessories (see also Special Accessories)



### Interface cable, RS232, crossed wired (null modem cable)

Connection cable for communication

- 2x D-Sub socket, 9-pin
- Cable length: 3.00 m

Ord.No. **X00010844**

**Protection cover for MT series 3xx/400/500**

To protect the front plate against mechanical collision during transport without transport case.

Ord.No. **100466700**

**Coaxial cable with BNC plug, 2 m**

- 2x BNC plug

Ord.No. **Z09548320**

## Documentation

**Complete Documentation**

as pdf files on USB flash drive

Ord.No. **100090716**

## Special Accessories

**Power cord with protective earth "stackable safety plug to IEC 60320 C13", 2,5 m**

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x brown, 1x blue, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067610**


**Power cord with protective earth "stackable safety plug to IEC 60320 C13", 2,5 m**

For supply via test voltage.

- 3x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve (1x red, 1x black, 1x yellow/green)
- 1x socket IEC 60320 C13

Ord.No. **100067611**

## Special Accessories (Quick Connection Cable)

**Quick connection cable for "current/rigid sleeve" for MT series, 12 A, 2.5 m, phase colours: yellow/green/violet**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve - 2x yellow, 2x green, 2x violet.

Ord.No. **100023476**

- Cable cross-section: 2.5 qmm




**Quick connection cable for “voltage/rigid sleeve” for MT series, 2.5 m, phase colours: yellow/green/violet/black**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x yellow, 1x green, 1x violet, 1x black
- Cable cross-section: 2.5 qmm

Ord.No. **100023418**



**Quick connection cable “current/rigid sleeve” for MT series, 12 A, 2.5 m, phase colours: black/brown/white**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x black, 2x brown, 2x white
- Cable cross-section: 2.5 qmm

Ord.No. **100023493**



**Quick connection cable “voltage/rigid sleeve” for MT series, 2.5 m, phase colours: brown/black/white/blue**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 4-pin connector with anti-twist safeguard.
- Mains side: 4x stackable, spring-loaded 4 mm plug with rigid insulating sleeve - 1x brown, 1x black, 1x white, 1x blue
- Cable cross-section: 2.5 qmm

Ord.No. **100023492**



**Quick connection cable “current/rigid sleeve” for MT series, 12 A, 2.5 m, phase colours: black/brown/grey**

**Reference meter > Unit under test.**

To prevent connecting faults on the instrument's side.

- Instrument's side: 1x 6-pin connector with anti-twist safeguard.
- Mains side: 6x stackable, spring-loaded 4 mm plugs with rigid insulating sleeve. 2x black, 2x brown, 2x grey
- Cable cross-section: 2.5 qmm

Ord.No. **100023474**

## Special Accessories (Current and Voltage Cables)



- Laboratory cable with stackable plug, green, 2.0 m**  
Measurement category III (CAT III).
- 2x stackable 4 mm plugs with rigid insulating sleeve
  - Lead cross section: 2.5 qmm

Ord.No. **X00006908**



- Laboratory cable with stackable plug, violet, 2.0 m**  
Measurement category III (CAT III).
- 2x stackable 4 mm plugs with rigid insulating sleeve
  - Lead cross section: 2.5 qmm

Ord.No. **X00006909**



- Laboratory cable with stackable plug, brown, 2.0 m**  
Measurement category III (CAT III).
- 2x stackable 4 mm plugs with rigid insulating sleeve
  - Lead cross section: 2.5 qmm

Ord.No. **100414100**



- Laboratory cable with stackable plug, grey, 2.0 m**  
Measurement category III (CAT III).
- 2x stackable 4 mm plugs with rigid insulating sleeve
  - Lead cross section: 2.5 qmm

Ord.No. **100414103**



- Laboratory cable with stackable plug, white, 2.0 m**  
Measurement category III (CAT III).
- 2x stackable 4 mm plugs with rigid insulating sleeve
  - Lead cross section: 2.5 qmm

Ord.No. **100662500**

## Special Accessories (Connectors)



### Connecting terminals for current

- Isolating screw joint for flexible wire connection max cable size 1,5 ... 16 mm<sup>2</sup>
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00011923**



### Adapter for terminal blocks

- Connection via insulated flexible copper conductor.
- Socket: 4 mm rigid socket in insulator, made of brass, accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **101584400**



### 4 mm plug adapter (banana plug)

- Plug: 4 mm spring-loaded plug, made of brass.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00004962**



### 4 mm cable lug adapters

- Cable lug adapter, made of brass for permanent installation, e. g. for connecting screw terminals.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00004963**



### Spring clip

- Connection via spring clip.
- Socket: spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **100606760**



### Test plugs for terminal blocks

- Plug: 4 mm test plug, made of brass with spring-loaded plug for connecting into rail mounted terminals with 4 mm sockets.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **100102400**



#### 4 mm test clips (crocodile clips), wide

- Crocodile clip made of brass with all-round insulation. Toothed jaws for wide grip with surface for fine wire.
- Socket: 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00010059**



#### 4 mm test clips (crocodile clips), slim

- Small, slim crocodile clip made of brass with all-round insulation. Toothed jaws for wide grip with surface for fine wire.
- 4 mm rigid socket in insulator accepting spring-loaded 4 mm plugs with rigid insulating sleeve.

Ord.No. **X00009329**



#### Accessories bag without content

DIN A6, material: polypropylene

Ord.No. **100214400**

#### Fuse, 3.15 A, 5 mm x 20 mm, time-lag



Ord.No. **M00460252**

### Special Accessories (Transport)



#### Accessories bag

Nylon bag with inlet from rigid foam, designed for

- Test leads
- Scanning head
- Current clamps
- Etc.

Overall dimensions: 41 cm x 31 cm x 16 cm (H x W x D)

*Please clarify whether the bag size is suitable for the ordered accessories.*

Ord.No. **100148209**

### Special Accessories (General)



**Adapter “USB to RS232” (32/64 bit), 1.5 m**  
For use with an external PC/Notebook (32/64 bit) with WINDOWS OS (7, 8, 10).

Ord.No. **101421801**

## Readjustment (for Service)




### Adjustment of MT500

Ord.No. **100033859**

*Note:* Calibration and Calibration report are not included.

## Calibration (for Service)




**Factory Calibration for MT500, 50 Hz**  
incl. ZERA calibration report.

Ord.No. **100519726**

**Load points according to ZERA regulations.**  
Summary of used load points can be downloaded at [www.zera.de](http://www.zera.de).

Additional load points are subject to charges.



**Factory Calibration for MT500, 60 Hz**  
incl. ZERA calibration report.

Ord.No. **100519727**

**Load points according to ZERA regulations.**  
Summary of used load points can be downloaded at [www.zera.de](http://www.zera.de).

Additional load points are subject to charges.




**Factory Calibration for instrument, each additional load point for power and energy**

Ord.No. **100007093**



**Factory Calibration**  
for instrument, each additional  
load point for current and/or voltage

Ord.No. **100007094**




**DAkks DKD-Calibration for MT500, 50 Hz**  
incl. DKD-Calibration Certificate acc. IEC 17025

Ord.No. **100519626**

**Load points according to ZERA regulations.**  
Summary of used load points  
can be downloaded at [www.zera.de](http://www.zera.de).

Additional load points are subject to charges.



**DAkks DKD-Calibration for MT500, 60 Hz**  
incl. DKD-Calibration Certificate acc. IEC 17025

Ord.No. **100519627**

**Load points according to ZERA regulations.**  
Summary of used load points  
can be downloaded at [www.zera.de](http://www.zera.de).

Additional load points are subject to charges.



**DAkks DKD-Calibration (acc. IEC 17025)**  
for instrument, each additional  
load point for power and energy

Ord.No. **100006893**



**DAkks DKD-Calibration (acc. IEC 17025)**  
for instrument, each additional  
load point for current / voltage

Ord.No. **100006894**

---

ZERA GmbH  
Humboldtstrasse 2a  
D-53639 Koenigswinter  
Phone: +49 (0)2244 9277-0  
E-Mail: [zera@zera.de](mailto:zera@zera.de)  
Internet: [www.zera.de](http://www.zera.de)  
Managing Director: Horst Wächter  
Headquarter: Königswinter

---

Commerzbank Bonn  
IBAN: DE29 3804 0007 0113 3131 00  
SWIFT (BIC): COBADEFF380

Kreissparkasse Köln  
IBAN: DE15 3705 0299 0001 0784 92  
SWIFT (BIC): COKSDE33

HRB 7073 Siegburg  
VAT-IdNo. DE 218 515 479  
WEEE-Reg.Nr. DE 53879641

---

## Notes on using the product catalogue

When ordering, always state the order number.

Pictures can differ from original product.

We follow ZVEI terms of delivery, see on [www.zera.de](http://www.zera.de)