

EMOB200 – Technical data

| General | |
|---|--|
| Temperature range, operation | -10° ... +40° C |
| Relative humidity (not condensing) | 10 ... 90 % |
| Dimensions (LxWxH) | 546 x 347 x 197 mm |
| Weight | 9,5 kg |
| Connector type | IEC 62196 Combo type 2 (type 2, CCS2) |
| Safety | |
| IP class according to DIN EN 60529 | IP67 [IP40] |
| Declaration of conformity | CE conform |
| Overvoltage category current measurement AC | CAT II 300 V |
| Overvoltage category current measurement DC | CAT I 1000 V |
| Voltage Measurement AC | |
| Voltage range(s) 23) 30) | 250 V, 8 V, 100 mV |
| Voltage measurement accuracy 11) 23) | < 0.05 % |
| Voltage measurement accuracy 11) 30) | < 0.025 % |
| Voltage measurement temperature drift 11) 23) | < 15 x 10 E-6 / K |
| Voltage measurement temperature drift 11) 30) | < 5 x 10 E-6 / K |
| Maximum of voltage AC | 300 V |
| Voltage Measurement DC | |
| Voltage measurement DC accuracy 23) 30) | < 0.05 % @ 200 V ... 1000 V < 0.1 % @ 100 V ... < 200 V |
| Voltage measurement DC temperature drift 3) 23) 30) | < 15 x 10-6 / K |
| Voltage measurement DC long term stability 3) 23) 30) | < 100 x 10-6 / Year |
| Maximum of voltage DC | 1200 V= |
| Current measurement AC | |
| Fundamental frequency | 45 ... 65 Hz |
| Current measurement | 10 mA ... 32 A |
| Current range(s) 23) | 50 A, 10 A, 5 A, 1 A, 500 mA, 100 mA, 50 mA |
| Current measurement accuracy 23) | < 0.05 % @ 32 A ... 100mA < 0.1 % @ 100 mA ... 20 mA |
| Current measurement accuracy 30) | < 0.025 % @ 32 A ... 100 mA < 0.05 % @ 100 mA ... 20 mA |
| Angle measurement accuracy 23) | < 0.015 ° @ 32 A ... 100mA < 0.03 ° @ 100mA ... 20 mA |
| Angle measurement accuracy 30) | < 0.01 ° @ 32 A ... 100mA < 0.03 ° @ 100mA ... 20 mA |
| Current measurement temperature drift 23) | < 15 x 10 E-6 / K |
| Current measurement temperature drift 30) | < 5 x 10 E-6 / K |
| Maximum current AC | 32 A ~ |
| Current channels surge current capability AC | 63 A (1 min) |
| Current measurement DC | |
| Current measurement DC accuracy 23) 30) | < 0.05 % @ 20 A ... 200 A < 0.1 % @ 1 A ... < 20 A |
| Maximum current DC | 200 A = |
| Current measurement DC temperature drift 4) 23) 30) | < 15 x 10-6 / K |
| Current measurement DC long term stability 23) 30) > 10 A | < 200 x 10-6 / Year |
| Current channels surge current capability DC | 280 A (1 min) |
| Power Measurement AC | |
| Power/energy measurement accuracy 23) | < 0.1 % @ 32 A ... 100 mA < 0.15 % @ 100 mA ... 20 mA |
| Power/energy measurement accuracy 30) | < 0.05 % @ 32 A .. 100 mA < 0.1 % @ 100 mA ... 20 mA |
| Power/energy measurement temperature drift 23) | < 30 x 10 E-6 / K |
| Power/energy measurement temperature drift 30) | < 10 x 10 E-6 / K |
| Power Measurement DC | |
| Power/energy measurement DC accuracy 3) 23) 30) | < 0.1 % @ 20 A ... 200 A < 0.15 % @ 1 A ... < 20 A |
| Power/energy measurement DC temperature drift 3) 4) 23) 30) | < 30 x 10-6 / K |
| Power/energy measurement DC long term stability 3) 23) 30) > 10 A | < 300 x 10-6 / Year |

3: From 200 V ... 1000 V

06.05.2024

4: From 1 A ... 200 A

11: From 30 V ... 300 V

23: In connection with MT310s2

30: In connection with MT320s2

Subjects to alteration.