

EMOB 80 – Technical data

General	
Temperature range, operation	-10° ... +40° C
Relative humidity (not condensing)	10 ... 90 %
Connector type	IEC 62196-2 type 1
Safety	
IP class according to DIN EN 60529	IP67 [IP40]
Declaration of conformity	CE conform
Overvoltage category current measurement	CAT II 300 V
Voltage Measurement	
Voltage range(s) 23) 30)	250 V, 8 V, 100 mV
Voltage measurement accuracy 11) 23)	< 0.05 %
Voltage measurement accuracy 11) 30)	< 0.025 %
Voltage measurement temperature drift 23)	< 15 x 10 E-6 / K
Voltage measurement temperature drift 30)	< 5 x 10 E-6 / K
Current measurement AC	
Fundamental frequency	45 ... 65 Hz
Current measurement	10 mA ... 80 A
Current range(s) 23) 30)	100 A, 50 A, 10 A, 5 A, 1 A, 500 mA, 100 mA, 50 mA
Current measurement accuracy 23)	< 0.05 % @ 80 A ... 100 mA
Current measurement accuracy 30)	< 0.025 % @ 80 A ... 100 mA
Angle measurement accuracy 23)	< 0.015 ° @ 80 A ... 100 mA
Angle measurement accuracy 30)	< 0.01 ° @ 80 A ... 100 mA
Current measurement temperature drift 23)	< 15 x 10 E-6 / K
Current measurement temperature drift 30)	< 5 x 10 E-6 / K
Maximum current	80 A ~
Current channels surge current capability	120 A (1 min)
Power Measurement AC	
Power/energy measurement accuracy 11) 23)	< 0.1 % @ 80 A ... 100 mA
Power/energy measurement accuracy 11) 30)	< 0.05 % @ 80 A .. 100 mA
Power/energy measurement temperature drift 23)	< 30 x 10 E-6 / K
Power/energy measurement temperature drift 30)	< 10 x 10 E-6 / K

11: From 30 V ... 300 V

23: In connection with MT310s2

30: In connection with MT320s2

Subjects to alteration.

16.02.2024

EMOB80_SPECS_EXT_GB_V4.02